

DECLARATION OF PERFORMANCE (DoP)
according to Construction Products Regulation (CPR) No 305/2011

DoPNo. 15/0320(2105) - en

1. Unique identification code of the product-type: **ResiFIX VY, VY Cool**
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
ETA-15/0320 [from 31.05.2021], annex A 2
Batch number: see packaging of the product.
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Generic type	Injection system incl. threading rods
For use in	Masonry covered sizes: anchor rods: M8, M10, M12, M16 sleeves SH: 12x80, 16x85, 16x130, 20x85, 20x130, 20x200
Option / Category	d/d, w/d, w/w
Loading	Static and quasi-static
Material	Anchor rod: <u>Zinc-plated steel:</u> dry internal conditions only Stainless steel A2 – 1.4301 / 1.4307 / 1.4311 / 1.4567 or 1.4541 <u>and stainless steel A4 – 1.4401 / 1.4404 / 1.4571 / 1.4362 or 1.4578:</u> internal and external use without particular aggressive conditions <u>Hot dip galvanized steel:</u> dry internal conditions only <u>High corrosion resistant steel (HCR) – 1.4529 / 1.4565:</u> internal and external use with particular aggressive conditions Sleeve: polypropylene
Temperature range <i>if applicable</i>	I: -40°C to +40°C (max. long term temp. +24°C, max. short term temp. +40°C) II: -40°C to +80°C (max. long term temp. +50°C, max. short term temp. +80°C) III: -40°C to +120°C (max. long term temp. +72°C, max. short term temp. +120°C)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

CELO Befestigungssysteme GmbH
Industriestrasse 6
86551 Aichach, Germany

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): --
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **system 1**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: --
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
Deutsches Institut für Bautechnik (DIBt), Berlin

issued:

ETA-15/0320 [from 31.05.2021]

on the basis of

EAD 330076-00-0604, edition 11/2017

The notified body 2873 performed under system 1:

- initial type testing of the product,
- initial inspection of factory and of factory production control,
- continuous surveillance, assessment and approval of factory production control.

9. Declared performance:

Essential Characteristics	Design Method	Performance	Harmonized Technical Specification
Characteristic values for resistance	EOTA TR 054, version April 2016	ETA-15/0320 [from 31.05.2021], annex C1 to C40	EAD 330076-00-0604, edition 11/2017
Displacements	EOTA TR 054, version April 2016	ETA-15/0320 [from 31.05.2021], annex C1 to C40	
Durability	EOTA TR 054, version April 2016	ETA-15/0320 [from 31.05.2021], annex B1	
Reaction to fire	DIN EN 13501-1	Class A1	
Content, emission and/or release of dangerous substances	ETAG 029	No performance assessed	

Where pursuant to Article 37 or 38 in the Specific Technical Documentation has been used, the requirements with which the product complies: --

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Achim Ruppertz
Marketing and Technical Manager

Aichach, 31.05.2021

